









IKARUS Transpa

Representation with lane guide item no. 60990 and limiter item no. 61000

Motorized gate, waist-high, glass panel

Especially suitable to provide access for strollers and wheel-chairs at attended indoor entrances to recreation facilities and in architecturally sensitive buildings.

- Central drive inside turnstile
- Quiet running, precise home position
- Pre-assembled on delivery
- Single or bidirectional operation
- Reversible entry direction
- High traffic capacity
- High quality and long service life
- Architecture-friendly transparence
- Maintenance-free mechanism
- Extensive line of accessories



Gotschlich Maschinenbau Ges.m.b.H

Feistlgasse 6, A-1210 Wien Tel. +43 (1) 2596518 eMail: office@gotschlich.at www.gotschlich.at

Functional Description:

The waist-high Ikarus Transpa motorized gate enhances turnstile installations, adding access for strollers and wheelchairs. It is made entirely of rust-free materials and is especially well suited for use in office buildings and recreation facilities such as fitness centers.

With the drive in the center pole and the glass panel barrier elements, the Ikarus Transpa has a stylish, open look that fits in easily with any architecture.

Ikarus Transpa is suitable for bidirectional operation and, due to the precise home position of the LOGITURN planetary gears, for paired double entrances.

Application Areas:

- Pools, Museums & Recreation
- Building Access Control
- Supply Facilities
- Trade Shows

Models:

6P950: Ikarus Transpa

Extras:

60990: Lane Guide

61000: Limiter Element

21670: Foundation Assembly for non-sustainable floors

for Ikarus, lane guide and limiter

21680: Foundation Assembly for non-sustainable floors

for the IKARUS drive column

8P408: External LOGITURN operating console

8P407: Housing for console

Suitable By-Products:

6P921: Vertikal Turnstile Gyro Transpa

21695: Reader Stand

Technical Characteristics:

Power Supply: 24 V DC

Power Consumption: max. 50 VA

Storage Temperature: -40°C bis +40°C Operating Temperature: +5°C bis +50°C

Width / Lane Width: 1.200 mm/950 mm

Length: 300 mm
Height: 900 mm
Mass: 110 kg

Reader Interface: Floating Contacts

Material: CrNi Steel Type 1.4301

Security Glass

